



IRIDEX

OcuLight® GL Laser

High Performance and Value

- Efficiency with a full 1500 mW of deliverable laser power
- Provides pulse durations and pulse intervals from 50 to 1000 milliseconds
- Expands system performance with convenient accessories
 - Includes a full line of delivery devices
 - Offers a broad selection of EndoProbe® handpieces for a variety of surgical procedures
 - Offers an optional wireless footswitch to reduce clutter and improve ergonomics and control
- Offers excellent ergonomics and true portability
 - Quiet operation eliminates distraction during treatment
 - Convenient, easily understood controls permit smooth interface with the laser system and delivery devices
 - Transports easily between treatment rooms and offices



OcuLight® GL Laser

Specifications

Wavelength:	532 nm Green
Weight:	<6.0 kg (13.2 lb)
Dimensions:	30 cm x 30 cm x 15 cm (12 in W x 12 in D x 6 in H)
Connector Type:	Resistor
Electrical:	100–240 VAC, 50/60 Hz
Cooling:	Whisper fan with peltier cooling
Exposure Duration:	CW-Pulse™: 30–1000 ms
Exposure Interval:	CW-Pulse: 30–1000 ms
Aiming Laser:	Diode laser, 635 nm nominal
Delivery Device	SLA: 0–1200 mW
Power Output:	LIO: 0–1500 mW EndoProbe®: 0–1500 mW

Specifications are subject to change without notice. OcuLight, EndoProbe, IRIDEX and the IRIDEX logo are registered trademarks and TruFocus and CW-Pulse are trademarks of IRIDEX Corporation.

Products are covered by one or more of the following U.S. patents: 5,085,492; 5,088,803; 5,372,595; 5,511,085; 5,521,932; 5,663,979; 6,540,391 B2; 6,377,599 B1; 6,327,291 B1; 6,222,869 B1; 6,144,484; 6,141,143; 5,999,554; 5,982,789; 6,733,490 B1; 6,800,076 B2; 7,537,593 B2; 7,771,417 B2; 7,766,904 B2; 7,909,813 B2.

Clinical references available upon request.



EC REP Emergo Europe
Prinsessegracht 20, 2514 AP, The Hague, The Netherlands

CE 0086



IRIDEX

Elegantly simple solutions™

